

# NO6610

## Inside one way vision film

### Description :

Film : 140micron Macromolecular PVC monochrome film  
Adhesive: Water based foam removable adhesive  
Liner : 36micron PET  
Width: 1.37m

### Features :

1. Environment-friendly adhesive with special process; Excellent color reproduction when printing on the glue side;
2. It can be pasted directly on inside glass to avoid damage and pollution;
3. One side visual, sun-shade and privacy protection; Hole size 1.40mm, perforation 30%;

### Application :

1. Apply for glass, also suitable for transparent acrylic plate、PVC、PET transparent plate and so on
2. This product is suitable for various solvent ink and Eco-solvent ink

### Technical :

Testing condition: Indoor temperature 23±2°C; Relative humidity 50±5%; Use aluminum, glass, steel plate as the base material for testing.

Test Items	Units	Test method	Average value
Thickness PVC	Micron	GB/T6672-2001	150±10
Weight-Liner	g/m <sup>2</sup>	GB4669-1995	140±10
Weight -finished product	g/m <sup>2</sup>	GB4669-1995	280±20
24h, 180°peel	N/25mm	FTM 1	≥4
Dimensional stability MD	mm	FTM 14	≤1.5
Dimensional stability CD	mm	FTM 14	≤1.0
Tensile strength MD	N/25 mm	GB/T1040.1-2006	≥35
Tensile strength CD	N/25 mm	GB/T1040.1-2006	≥20
Construction Temperature	°C		20±10
Applicable Temperature	°C		-20 ~ +70

All technical data is subject to change without prior notice

### Storage condition :

All NAR products always need to be stored in the original packing and with the original protection materials, preferably stored hermetically, no more than 6 layers if stored horizontally. Do not expose in direct sunlight or heat sources. Shelf life will be two year with temperature of 25°C±5°C and relative humidity of 50±15%.

### Production and Application Environment :

Production environment: temperature of 25±5°C, relative humidity of 50%±10%, clean dust-free environment without suspended matter; please move the materials to the printing environment 24 hours before printing. Test prior to use and remain enough edge margins when printing.

Application environment: temperature of 20±10°C, relative humidity of 50±10%; Pasting on flat, smooth and clean surface without floating dust and shedding; It is necessary to take more than 2 hours for maintenance before laminating.

**Warranty Condition :**

- 1、Warranty date is two years: One way vision products need accord with storage condition, preferably use with six months
- 2、Prosecution date : from the product manufacture date, no-acceptance for overdue product.

**Important remark: :**

The information mentioned in this product data sheet is based upon tests that were executed by NAR, and that we consider to be reliable.  
Environment humidity more than 70% in different district will decrease the printing result.

**Product application :**

**NAR**  
IDEAS FOR SIGN